OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ASCO - 2/2 PROPORTIONAL VALVE 1/8"

SCG202A201VS3
Proportional valve 2/2 NC 1/8" 24VDC

- Normally closed
- Compact version
- Working pressure 0 to 8 bar
- Housing in brass or stainless



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	1/8 BSP
Flow factor / flow coefficient	0,05
IP class	IP65

MATERIAL DATA

Material body	Brass
Material seat	Brass

TEMPERATURE DATA

Temperature of media from	0 °C
Temperature of media to	50 °C

ADDITIONAL DATA

Pressure max	35 bar
Viscosity max	50 cSt
Weight	0.2 kg

Power consumption	6.3 W

Throughput	1.2 mm
Sensitivity	<1%
Voltage dc	24 V
Temperature operational min	0 °C
Temperature operational max	40 °C
Material coil	Epoxy
Differential air pressure max	8 bar
Differential pressure min	0 bar
Differential oil pressure max	5 bar
Differential pressure vacuum max	1 bar
Differential water pressure max	5 bar
Flow max	0.7 l/min
Function 1	2/2
Function 2	Normally Closed
Material plunger	Stainless steel
Material glide ring	PTFE
Material seat seal	FPM
Material spring	Stainless steel



