



ASCO - 2/2 PROPORTIONAL VALVE 3/8"

SCB202A036VS3

Proportional valve 2/2 NC 3/8" 24VDC

- Normally closed
- Large flow
- Working pressure 0 to 4 bar
- Housing in brass or stainless



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Connection	3/8 NPT
Flow factor / flow coefficient	0,72
IP class	IP65

MATERIAL DATA

Material body	Stainless steel 303
Material of seals	FPM
Material seat	Stainless steel

TEMPERATURE DATA

Temperature of media from	-10 °C
Temperature of media to	90 °C

ADDITIONAL DATA

Pressure max	35 bar
Viscosity max	21 cSt
Weight	0.65 kg

Power consumption	8 W
Throughput	5.6 mm
Sensitivity	<2%
Voltage dc	24 V
Temperature operational min	-10 °C
Temperature operational max	75 °C
Material coil	Epoxy
Differential air pressure max	1.4 bar
Differential pressure min	0 bar
Differential pressure vacuum max	1 bar
Flow max	12 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
Material plunger	Stainless steel
Material glide ring	PTFE
Material spring	Stainless steel