

OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ASCO - FLOWTRONIC D PROGRAMMABLE PROPORTIONAL VALVE FOR FLOW REGULATION

60701017 Flowtronic,G1/4",500NI,4-20mA + displ.

- · Direct operating
- Rapid and accurate pressure regulation
- Simple optimisation of regulation parameters
- · LED display



PRODUCT DESCRIPTION

Flowtronic^D, with its direct operating solenoid regulates flow with high accuracy and short response time. The regulation parameters can be easily adjusted via a PC allowing the regulator to be set optimally for each individual application. Flowtronic^D can, naturally, be used without software; flow is then set using push buttons on the regulator operation panel. The regulator has auto-tune, which automatically regulates the current to the coil for optimal regulation, as well as fault indication via LEDs on the control panel. Available with or without a display.


CONNECTION

Pin	Description	Cable 2 m (5 wires)	Cable 5 m (6 wires)
1	Supply 24 V DC	brown	brown
2	Analogue signal, input	white	white
3	Earth, supply	blue	green
	Earth, analogue control signal*		yellow
4	Analogue signal, output	black	pink
5	Digital output (pressure switch)	grey	grey
Housing	Screening (EMC)	screen	screen

TECHNICAL DATA

Connection	G1/4			
IP class	IP65			
MATERIAL DATA				
Material of seals	NBR			
Material internal parts	Aluminium, Brass, Stainless steel			
TEMPERATURE DATA				
Temperature of media from	0 °C			
Temperature of media to	50 °C			
ADDITIONAL DATA				
Pressure max	8 bar			
Response time	200 ms			
Weight	1.85 kg			
Power consumption	30 W			
Throughput	5 mm			
Voltage dc	24 V			
Temperature operational min	0 °C			
Temperature operational max	40 °C			
Flow max	500 l/min			
Load max	1250 mA			

Aluminium



Material of body