

## BANICO GAS SOLENOID VALVE ZEV SERIES

ZEV40

1.1/2 BSP, 360mBar, 2-way, Normally Closed

- Max pressure to 360 mbar
- Suitable for a variety of gases
- Two way normally closed design
- Available in sizes from 3/8" to 3" in Automatic



### PRODUCT DESCRIPTION

Fast Acting Design with max pressure to 360 mbar. Automatic gas solenoid valves are used for safety and control of gas for shut-off in gas feed pipes. Suitable for various gases, including Natural Gas, Propane and LPG Gas. Two way normally closed design. Fitted with 1/4" plug ports for pressure gauge and fitting to proving and interlock system. Available in sizes from 3/8" to 3" in Automatic (up to 8" in Flanged)

## TECHNICAL DATA

### GENERAL DATA

Function	2-way, Normally Closed (SPST)
Connection	1 1/2 BSP
IP class	IP54

### MATERIAL DATA

Material body	Die cast aluminium
Material of seals	NBR

### TEMPERATURE DATA

Temperature ambient from	-15 °C
Temperature ambient to	60 °C

### ADDITIONAL DATA

Pressure max	360 bar
--------------	---------

<b>Weight</b>	5 kg
<b>Power consumption</b>	42 W
<b>Response time</b>	<1 second
<b>Voltage AC</b>	230 V
<b>Cable entry</b>	PG11 Live, Neutral, Earth
<b>Length</b>	150 mm
<b>Height</b>	214 mm
<b>Material of filter</b>	Stainless steel 303
<b>Material spring</b>	Stainless Steel 302
<b>Max number of operations per minute</b>	20