

BANICO AUTOMATIC GAS VALVE ZEVF SERIES

ZEVF65

ZEVF, 2 1/2" Flanged PN16, 360, 2-way, Normally Closed

- Max pressure to 360 mbar
- Suitable for a variety of gases
- Two way normally closed design
- Available in sizes from 3/8" to 3" in Automatic



PRODUCT DESCRIPTION

Flanged gas solenoid valve from Banico Controls in an automatic and two way normally closed design. Used for safety and control of gas for shut-off in gas feed pipes. Suitable for various gases, including Natural Gas, Propane and LPG Gas.

TECHNICAL DATA

GENERAL DATA

Function	2-way, Normally Closed (SPST)
Connection	2 1/2" Flanged PN16
IP class	IP54

MATERIAL DATA

Material body	Die cast aluminium
Material of seals	NBR

TEMPERATURE DATA

Temperature ambient from	-15 °C
Temperature ambient to	60 °C

ADDITIONAL DATA

Pressure max	360 bar
--------------	---------

Weight	15 kg
Power consumption	72 W
Response time	<1 second
Voltage AC	230 V
Cable entry	PG11 Live, Neutral, Earth
Length	310 mm
Height	343 mm
Material of filter	Stainless steel 303
Material spring	Stainless Steel 302
Max number of operations per minute	20