

## BANICO AUTOMATIC GAS VALVE ZEVF SERIES

ZEVF100

ZEVF, 4" Flanged PN16, 360, 2-way, Normally Closed



- Max pressure to 360 mbar
- Suitable for a variety of gases
- Two way normally closed design
- Available in sizes from 3/8" to 3" in Automatic



### PRODUCT DESCRIPTION

Flanged gas solenoid valve from Banico Controls in an automatic and two way normally closed design. Used for safety and control of gas for shut-off in gas feed pipes. Suitable for various gases, including Natural Gas, Propane and LPG Gas.

### TECHNICAL DATA

#### GENERAL DATA

Function	2-way, Normally Closed (SPST)
Connection	4" Flanged PN16
IP class	IP54

#### MATERIAL DATA

Material body	Die cast aluminium
Material of seals	NBR

#### TEMPERATURE DATA

Temperature ambient from	-15 °C
Temperature ambient to	60 °C

#### ADDITIONAL DATA

Pressure max	360 bar
--------------	---------

<b>Weight</b>	36.4 kg
<b>Power consumption</b>	175 W
<b>Response time</b>	<1 second
<b>Voltage AC</b>	230 V
<b>Cable entry</b>	PG11 Live, Neutral, Earth
<b>Length</b>	350 mm
<b>Height</b>	384 mm
<b>Material of filter</b>	Stainless steel 303
<b>Material spring</b>	Stainless Steel 302
<b>Max number of operations per minute</b>	20