

## BANICO AUTOMATIC GAS VALVE ZEVF SERIES

ZEVF125

ZEVF, 5" Flanged PN16, 200, 2-way, Normally Closed

- Max pressure to 360 mbar
- Suitable for a variety of gases
- Two way normally closed design
- Available in sizes from 3/8" to 3" in Automatic



### PRODUCT DESCRIPTION

Flanged gas solenoid valve from Banico Controls in an automatic and two way normally closed design. Used for safety and control of gas for shut-off in gas feed pipes. Suitable for various gases, including Natural Gas, Propane and LPG Gas.

## TECHNICAL DATA

### GENERAL DATA

Function	2-way, Normally Closed (SPST)
Connection	5" Flanged PN16
IP class	IP54

### MATERIAL DATA

Material body	Steel
Material of seals	NBR

### TEMPERATURE DATA

Temperature ambient from	-15 °C
Temperature ambient to	60 °C

### ADDITIONAL DATA

Pressure max	200 bar
--------------	---------

<b>Weight</b>	108 kg
<b>Power consumption</b>	290 W
<b>Response time</b>	<1 second
<b>Voltage AC</b>	230 V
<b>Cable entry</b>	PG11 Live, Neutral, Earth
<b>Length</b>	400 mm
<b>Height</b>	592 mm
<b>Material of filter</b>	Stainless steel 303
<b>Material spring</b>	Stainless Steel 302
<b>Max number of operations per minute</b>	20