



## EMERSON ASCO SOLENOID VALVE SERIES D144

### Total Isolation Valve

D144D4BI530L5A  
D144D4-Z530A... 2/2 N.C., G1/4", 0-10 bar, 0.32Kv,  
EPDM, 110V/50Hz, IP65,

- 2/2 Normally Closed G1/4 or Barbed Port
- Direct Acting, Total Isolation
- Suitable To Shut Off Liquid & Gaseous Fluids
- Operating Pressure Differential: Up to 10 Bar
- IP65



### PRODUCT DESCRIPTION

The Emerson ASCO D144 Series is a line of direct-acting, total isolation solenoid valves engineered for the precise control of aggressive or contamination-sensitive fluids. Featuring a 2/2 normally closed configuration, these valves offer port options including G1/4 and barbed connections, accommodating diverse installation needs. The design ensures that the actuator is completely isolated from the fluid, with only the body and lever-seal in contact, thereby preventing contamination and enhancing durability. Constructed with materials such as polyetherimide (PEI) for the body and various sealing options like EPDM, VMQ, or FPM, the D144 Series can handle operating pressure differentials up to 10 bar and fluid temperatures ranging from -10°C to +100°C.

Additionally, these valves are rated IP65, signifying robust protection against dust and water ingress.

These attributes make the ASCO D144 Series particularly suitable for industrial applications requiring reliable shut-off of liquid and gaseous fluids. Industries such as food processing, biotechnology, chemical and pharmaceutical manufacturing, and medical device production can benefit from the valves' ability to manage aggressive media without risk of contamination. The combination of total isolation design, versatile port options, and high-quality materials ensures that these solenoid valves deliver consistent performance in demanding environments where maintaining fluid purity and system integrity is critical.

## TECHNICAL DATA

### GENERAL DATA

Function	2/2, Normally Closed (SPST)
Connection	G1/4
Electrical connection	DIN 46340 - 3 Pole Plug Connector
Operating Pressure Differential	0-10 bar
Flow factor / flow coefficient	0,32
Coil type	Z530A
Voltage / Frequency	110/50 Hz
IP class	IP65

### MATERIAL DATA

Material body	PEI
Material of seals	EPDM
Encapsulation material	Fiberglass reinforced PET

TEMPERATURE DATA

Temperature ambient from	-10 °C
Temperature ambient to	60 °C
Temperature of media from	-10 °C
Temperature of media to	100 °C

ADDITIONAL DATA

Power consumption	Inrush: 23vA Holding: 14vA
Pressure max	12 bar
Response time	25 ms
Close delay	25 ms
Viscosity max	37 cSt
Continuous duty	ED 100%
Insulation class	F (140°C)
Weight	0.255 kg