

DATALOGIC - SG4-BODY COMPACT BASE

SG4-S4-090-PP-X
957851620 Type 4 Body Det 4-Beam 900mm
Protection Height

- Body protection (2, 3 and 4 beam), Type 4, PL e
- Range 0.5-50 m
- Protective height 500-800-900-1200 mm



PRODUCT DESCRIPTION

Datalogic safety light curtain SG4-BODY COMPACT Base is made for body detection with a range of up to 50 meters. The safety light curtain is available as type 4, and maintains highest level PL e according to the latest safety standards, EN ISO 13849-1 and EN 62061.

SG4-BODY COMPACT Base has a compact housing with basic functions as integrated manual reset /automatic reset and input for monitoring of external contactors (EDM). Configurations will be made by DIP switches.

SG4-BODY COMPACT models are provided in 2 different versions: Base and Muting.

SG4-BODY COMPACT Base safety light curtain include two safe electronic short-circuit detection outputs (PNP). If potential free contacts are needed We can offer forexample Datalogic safety relay CSME. Safety light curtain supplied complete with standard bracket.

Datalogic has a 3 year warranty for safety light curtains.

TECHNICAL DATA

Approvals	CE, cULus, TÜV
Cable connection receiver	M12, 4-pole
Cable connection transmitter	M12, 4-pole
Cable length max	50 m
Contact current max	0.5 A
DC	98,90%
Function	Automatic restart
In compliance with	EMC, LVD, MD
IP class	IP65
Material of body	Aluminium

MTTFd	384 year(s)
Number of beams	4
PL	e (EN ISO 13849-1)
Power consumption	Transmitter max 0,9 W . Receiver 2,2 W (without load)
Protection height	900 mm
Reaction time	16 ms
Resolution	315 mm
Safe outputs	2 OSSD
Sensing distance	0,5-50 m
SFF	99,38%
SIL	3 (EN IEC 61508)
Storage temperature max	70 °C
Storage temperature min	-25 °C
Supply voltage	24 V DC
T1 (Life time in years)	20
Temperature operational max	55 °C
Temperature operational min	-10 °C
Type	4
Voltage tolerance	±20 %

