

DATALOGIC - SG2-B 50/90

SG2-50-045-OO-X
957801130 Type 2 50mm Res 450mm Protection
Height

- Range up to 19m
- Protection height 150-1800 mm
- Type 2 (PLc SIL 2)
- Suitable for detection of personnel in a dangerous area



PRODUCT DESCRIPTION

SG2-B 50/90 is suitable for detection of personnel in a dangerous area (i.e. horizontal detection of a person standing in a dangerous area) with a range of up to 19 metres.

This Type 2 light curtain maintains level PLc according to the latest safety standards, EN ISO 13849-1 and EN 62061.

SG2-B 50/90 has basic functionality with two OSSD (PNP) safety outputs and manual reset.

TECHNICAL DATA

Additional features	Reset, test
Approvals	CE, cULus, TÜV
Cable connection receiver	M12, 5-pole
Cable connection transmitter	M12, 4-pole
Cable length max	50 m
Contact current max	0.5 A
DC	97,50 %
In compliance with	EMC, LVD, MD
IP class	IP65
LED indication	6 x LED
Material of body	Aluminium

MTTFd	273 year(s)
Number of beams	7
PL	c (EN ISO 13849-1)
Power consumption	Transmitter 2W, receiver 3,5W (without load)
Protection height	450 mm
Range	0,2-19 m
Reaction time	10 ms
Resolution	50 mm
Safe outputs	2 x OSSD
SIL	1 (EN IEC 62061)
Supply voltage	24 V DC, stabilized
T1 (Life time in years)	20
Temperature operational max	55 °C
Temperature operational min	-10 °C
Type	2
Voltage tolerance	±20 %

