

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## DATASENSING SH4-BODY BASE SAFETY LIGHT CURTAIN

SH4-3-0800-S-8 SH4 Body Standard 3-beam 800mm Protection Height

- Body detection, Type 4, PL e
- Operating distance: 70 m
- Temperature range: -30...+55 °C
- Basic functions, 2x OSSD Safety Outputs



## PRODUCT DESCRIPTION

Datasensing's SH4-BODY safety light curtain is designed for body/pedestrian access. The maximum distance between the emitter and receiver is 70m. SH4 Safety light curtains do not have a dead zone at the top or bottom of the emitter/receiver.

## **TECHNICAL DATA**

| Function          | Manual/automatic restart, EDM |
|-------------------|-------------------------------|
| IP class          | IP65, IP67                    |
| Material of body  | Aluminium                     |
| MTTFd             | 43 year(s)                    |
| Number of beams   | 3                             |
| PL                | e                             |
| Protection height | 800 mm                        |
| Reaction time     | 15 ms                         |
| Sensing distance  | 15 / 70m                      |
| SIL               | 3                             |
| Supply voltage    | 24 V DC                       |
| Weight            | 1.4 Kg/mt (single bar)        |
| Voltage tolerance | ± 20%                         |



| RECEIVER<br>STANDARD    | EMITTER                   |
|-------------------------|---------------------------|
| RX M12 MALE 8 PIN       | TX M12 MALE 5 PIN         |
|                         |                           |
| - RESET/RESTART (white) | 1 - 24V (brown)           |
| 2- 24V (brown)          | 2 - TEST (white)          |
| 3- EDM SEL (green)      | 3 - 0V (blue)             |
| 4- EDM (yellow)         | 4 - NOT CONNECTED (black) |
| 5- OSSD1 (grey)         | 5 - COM (grey)            |
| 5- OSSD2 (pink)         |                           |
| 7- 0V (blue)            |                           |
| 8- MAN_AUTO (red)       |                           |

