

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

DATASENSING SH4-BODY BASE SAFETY LIGHT CURTAIN

SH4-4-0900-S-8 SH4 Body Standard 4-beam 900mm Protection Height

- Body detection, Type 4, PL e
- Operating distance: 70 m
- Temperature range: -30...+55 °C
- Basic functions, 2x OSSD Safety Outputs



PRODUCT DESCRIPTION

Datasensing's SH4-BODY safety light curtain is designed for body/pedestrian access. The maximum distance between the emitter and receiver is 70m. SH4 Safety light curtains do not have a dead zone at the top or bottom of the emitter/receiver.

TECHNICAL DATA

| Function | Manual/automatic restart, EDM |
|-------------------|-------------------------------|
| IP class | IP65, IP67 |
| Material of body | Aluminium |
| MTTFd | 43 year(s) |
| Number of beams | 4 |
| PL | e |
| Protection height | 900 mm |
| Reaction time | 15 ms |
| Sensing distance | 15 / 70m |
| SIL | 3 |
| Supply voltage | 24 V DC |
| Weight | 1.4 Kg/mt (single bar) |
| Voltage tolerance | ± 20% |



| RECEIVER STANDARD | EMITTER |
|--------------------------|---------------------------|
| RX M12 MALE 8 PIN | TX M12 MALE 5 PIN |
| | |
| 1- RESET/RESTART (white) | 1 - 24V (brown) |
| 2-24V (brown) | 2 - TEST (white) |
| 3- EDM SEL (green) | 3 - 0V (blue) |
| 4- EDM (yellow) | 4 - NOT CONNECTED (black) |
| 5- OSSD1 (grey) | 5 - COM (grey) |
| 6- OSSD2 (pink) | |
| 7- 0V (blue) | |
| 8- MAN_AUTO (red) | |

