0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# **DATASENSING SH4-BASE HAND** PROTECTION SAFETY LIGHT CURTAIN

SH4-30-0600-B-5 SH4 Base Type 4 30mm Resolution 600mm Protection Height

- Hand protection (R30), range 0.2-20 m
- Protection height 300-2250mm
- Temperature Range from -30 to +55 °C
- 2 x OSSD safety outputs



### PRODUCT DESCRIPTION

Datasensing's SH4-BASE is a simple safety light curtain. All you need is a supply voltage for the emitter and receiver and from the receiver you get your safety outputs. (2 x OSSD)

The Hand protection resolution is 30mm and the maximum distance between the emitter and receiver is 20m.

SH4 Safety light curtains do not have a dead zone, they detect throughout the entire length of the light curtain.

## **TECHNICAL DATA**

Function	Automatic restart
IP class	IP65, IP67
Material of body	Aluminium
MTTFd	43 year(s)
Number of beams	24
PL	е
Protection height	600 mm
Reaction time	9 ms
Resolution	30 mm
Sensing distance	0,2-20 m
SIL	3
Supply voltage	24 V DC

Temperature operational max	55 °C
Temperature operational min	-30 °C
Voltage tolerance	± 20%

