

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk



DATASENSING SH4-BASE FINGER PROTECTION SAFETY LIGHT CURTAIN

SH4-14-2250-B-5 SH4 Base Type 4 14mm Resolution 2250mm Protection Height

- Finger protection (R14), range 0.2-10 m
- Controlled height 300-2250mm
- Temperature Range from -30 to +55 °C
- 2 x OSSD safety outputs



PRODUCT DESCRIPTION

Datasensing's SH4-BASE is a simple safety light curtain. All you need is a supply voltage for the emitter and receiver and from the receiver you get your safety outputs. (2 x OSSD)

The finger protection resolution is 14mm and the maximum distance between the emitter and receiver is 10m.

SH4 Safety light curtains do not have a dead zone, they detect throughout the entire length of the light curtain.

TECHNICAL DATA

Function	Automatic restart	
Material of body	Aluminium	
MTTFd	43 year(s)	
Number of beams	225	
PL	e	
Protection height	2250 mm	
Reaction time	29 ms	
Resolution	14 mm	
Sensing distance	0,2-10 m	
SIL	3	
Supply voltage	24 V DC	
Temperature operational max	55 °C	

Temperature operational min	-30 °C

± 20%

Voltage tolerance

RECEIVER BASE	EMITTER
RX M12 MALE 5 PIN	
1 - 24V (brown)	1 - 24V (brown)
2 - OSSD1 (white)	2 - TEST (white)
3 - 0V (blue)	3 - 0V (blue)
4 - OSSD2 (black)	4 - NOT CONNECTED (black)
5 - COM (grey)	5 - COM (grey)

