

0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk



## **DATASENSING SH4-BASE HAND PROTECTION SAFETY LIGHT CURTAIN**

SH4-30-0750-B-5 SH4 Base Type 4 30mm Resolution 750mm Protection Height

- Hand protection (R30), range 0.2-20 m
- Protection height 300-2250mm
- Temperature Range from -30 to +55 °C
- 2 x OSSD safety outputs



## PRODUCT DESCRIPTION

Datasensing's SH4-BASE is a simple safety light curtain. All you need is a supply voltage for the emitter and receiver and from the receiver you get your safety outputs. (2 x OSSD)

The Hand protection resolution is 30mm and the maximum distance between the emitter and receiver is 20m.

SH4 Safety light curtains do not have a dead zone, they detect throughout the entire length of the light curtain.

## **TECHNICAL DATA**

Function	Automatic restart
IP class	IP65, IP67
Material of body	Aluminium
MTTFd	43 year(s)
Number of beams	30
PL	e
Protection height	750 mm
Reaction time	9 ms
Resolution	30 mm
Sensing distance	0,2-20 m
SIL	3
Supply voltage	24 V DC

Temperature operational max	55 °C
Temperature operational min	-30 °C
Voltage tolerance	± 20%

RECEIVER BASE	EMITTER
RX M12 MALE 5 PIN	TX M12 MALE 5 PIN
1 - 24V (brown)	1 - 24V (brown)
2 - OSSD1 (white)	2 - TEST (white)
3 - 0V (blue)	3 - 0V (blue)
4 - OSSD2 (black)	4 - NOT CONNECTED (black)
5 - COM (grey)	5 - COM (grey)

r			ķ		i Et		
	24 (000000) (-0	04-010-0-0-0	=0==01=01=0000000000000000000000000000	<u></u>			000100000000 <mark>=0=0]</mark>
17	MORE	Lines			4000.	Litera	
25 (2800)	316.30-0205-0-0	100			#000L	107	
4 <u>7</u> - 429400	100-10-000-0-0 100-10-000-0-0	107 475			MCCCL. Des 194100-1-0 Des 10-bell 2-0	10 10	
	500 10 4200 8-4 900 10 400 5-3 900 10 400 5-3	0 0 0			MODEL Anna 10 4000 4.0 from 10 4000 4.0 from 10 4000 4.0	0 0	
	100 10 400 4 4 100 10 400 4 4 100 10 400 4 4 100 10 400 4 4	1 4 3 2			40000. Janu 30-000 6.0 Janu 30-000 6.0 Janu 30-000 6.0 Janu 30-000 6.0	1 ( 3 2	•
	106, 25, 4200, 5, 4 906, 35, 4600, 5, 5 906, 35, 4200, 5, 5 906, 35, 4700, 5, 5 906, 35, 4700, 5, 5	17 47 43 43 45 45			MODEL Des 19 dates 4.4 Des 19 dates 4.4 Des 19 dates 4.4 Des 19 dates 4.4 Des 19 dates 4.4	1 4 3 5 5 8	
98 <b>5</b> - 1986-199	Dec 21 (2003) 1.0 Dec 21 (2003) 1.0	107 405 414 715 409 409			#0000. Janu 24 com 4.4 Hanu 34 com 4.4 Hanu 24 com 4.4 Hanu 24 com 5.4 Hanu 24 com 5.4 Hanu 34 com 5.4 Hanu 34 com 5.4 Hanu 34 com 5.4	17 47 47 47 75 49 49	
2	100, 20 (200, 1.0) 100, 20 (200, 1.0)	air eile Gal Th Gan Gan Can			ACCOL To the Partial And The Reference of The Reference of The Reference The Reference of The Reference of The Reference The Reference of The Reference of The Reference The Reference of The Reference of The Reference of The Reference The Reference of The Reference of The Reference of The Reference The Reference of The Reference o	10 43 43 43 43 55 56 56 50 50 50 50 50 50 50 50 50 50 50 50 50	
	Dec 21 (2003) 1.0 Dec 21 (2003) 1.0	107 405 414 715 409 409			#0000. Janu 24 com 4.4 Hanu 34 com 4.4 Hanu 24 com 4.4 Hanu 24 com 5.4 Hanu 24 com 5.4 Hanu 34 com 5.4 Hanu 34 com 5.4 Hanu 34 com 5.4	17 47 47 47 75 49 49	
	Dec 24 4000 8.0 Dec 35 400 8.0 Dec 35 400 8.0	100 400 734 400 400 400 400 7300 500 500 500			40000, 1998, 50,000,50 1998, 50,000,50 1998, 50,000,50 1998, 50,000,50 1998, 50,000,50 1998, 50,000,50 1998, 50,000,50 1998, 50,000,50	907 419 414 174 174 190 190 100 100 100	
	Dei 24 200 8.0 Ben Halls 3.0 Ben Hall 3.0	Sim elan Tea Tean Ean Ean Ean Ean Ean Ean Ean Ean			40003. 2015 2015 6 1 1111 2016 7 1 1112 2016 7 1	107 414 116 116 116 116 116 116 116 116 116	
2	2010 20 4000 20 4 1000 20 4000 24 4 1000 20 1000 24 4 1000 20 1000 24 4 1000 20 1000 24 4 1000 20 4000 24 4 1000 20 4000 24 4 1000 20 4000 24 4	50 40 40 50 50 50 100 100 100 100 100 100 100 1			4000.	97 48 48 49 49 49 49 49 49 19 19 19 19 19 19 19 19 19 19 19 19 19	
	500 20 4000 4.0 400 20 4000 4.0 500 20 400 4.0 500 20 400 4.0 500 20 500 4.0 500 20 500 4.0 500 20 50 50 50 500 20 50 50 500 20 50 500 20 500 20	Sim elan Tea Tean Ean Ean Ean Ean Ean Ean Ean Ean			40000. 3011 - 2010 - 2.4 1011 - 3.0 1011 - 3.0 101	10* 41+ 115 124 124 124 124 124 124 124 124 124 124	