

DATASENSING SH4-STANDARD HAND PROTECTION SAFETY LIGHT CURTAIN

SH4-30-2250-S-8
SH4 Standard Type 4 30mm Resolution 2250mm
Protection Height

- Hand protection (R30), range 0.2-20 m
- Protection height 300-2250mm
- Temperature Range from -30 to +55 °C
- 2 x OSSD safety outputs



PRODUCT DESCRIPTION



With Datasensing's SH4-STANDARD safety light curtain, you can select between manual/automatic reset function and EDM monitoring for external contacts if required. The functions are selected by the receiver connections.

The hand protection resolution is 30mm and the maximum distance between the emitter and receiver is 20m.

SH4 Safety light curtains do not have a dead zone, they detect throughout the entire length of the light curtain.

TECHNICAL DATA

Function	EDM, Manual/automatic restart
Material of body	Aluminium
MTTFd	43 year(s)
Number of beams	90
PL	e
Protection height	2250 mm
Reaction time	17 ms
Resolution	30 mm
Sensing distance	0,2-20 m
SIL	3
Supply voltage	24 V DC
Temperature operational max	55 °C
Temperature operational min	-30 °C

RECEIVER STANDARD	EMITTER
RX M12 MALE 8 PIN	TX M12 MALE 5 PIN
	
1 - RESET/RESTART (white)	1 - 24V (brown)
2 - 24V (brown)	2 - TEST (white)
3 - EDM SEL (green)	3 - 0V (blue)
4 - EDM (yellow)	4 - NOT CONNECTED (black)
5 - OSSD1 (grey)	5 - COM (grey)
6 - OSSD2 (pink)	
7 - 0V (blue)	
8 - MAN_AUTO (red)	

