

DEHN LIGHTNING & SURGE PROTECTION FOR DC SIGNALS AND DATA LINES

BLITZDUCTOR, DEHNrapid, DEHNpatch, DEHNgate

929166

Surge protection DEHNpatch C8 D 4PPOE Compact combined arrester for the protection of data interfaces against lightning currents and surges in Ethernet applications up to 1GBit and Power over Ethernet (up to 4PPoE). Protection of 4 pairs via RJ45 sockets. Class D



- Protection devices for analogue signals
- Data network in line protection
- DC power protection
- Ethernet and PoE protection
- Ex-rated Versions

PRODUCT DESCRIPTION

The Blitzductor connect compact series, such as the BCO CL2 B-180, are ultra-slim surge arresters (just 6 mm wide) designed to protect up to two single-line circuits (e.g., shielded data or equipotential bonding lines). They feature tool-free push-in connections for fast installation, built-in LifeCheck and visual status LEDs, and optional remote signalling ensuring maintenance teams always know whether the unit is operational. These Type 1 SPDs meet EN/IEC 61643-21 and 22 standards, support impulse categories C2, C3, B2, and D1, and handle continuous operating voltages up to 180 V DC/127 V AC. In the event of surges, they can divert up to 5 kA (8/20 μ s) per line, 10 kA total, and lightning impulses up to 1.5 kA per line (3 kA total).

These surge arresters safeguard sensitive control, I/O, or communication lines in industrial and automation environments, particularly where space is limited and system uptime is critical. Their vibration- and shock-resistant polyamide housing and approvals for intrinsically safe (ATEX/IECEx) zones make them ideal for harsh or hazardous sites. Other versions in the series protect balanced or high-frequency pairs, DC supplies, or intrinsically safe circuits—ensuring tailored protection across measurement, fieldbuses, PoE links, or unbalanced analog cabling. Remote-monitor integration means fault status can be centrally tracked, minimizing downtime and maintenance costs.

TECHNICAL DATA

TECHNICAL DATA

| | |
|----------------------|----------------|
| Earthing arrangement | 35mm DIN rails |
| Nominal voltage | 3.3V |

DIMENSIONS

| | |
|--------|-------|
| Length | 51 mm |
| Width | 19 mm |
| Height | 75 mm |

ADDITIONAL DATA

| | |
|-------------|----------|
| Tariff code | 85363010 |
| Weight | 0.167 kg |

