



ASCO - COAXIAL VALVES

SCG287A010

- G3/8 - G1
- Temperature -20 to 100 ° C
- Pressure 0 to 40 bar
- Medium water, oil, gases
- Brass or stainless steel body



PRODUCT DESCRIPTION

Coaxial valves are used in applications for high pressure and high flows. The coaxial valve can accommodate flow in both directions. Coaxial valves are available in electrically controlled versions and pressure controlled namur versions.

Model SCG287

Function



- Brass/stainless
- 2/2 normally closed/open
- 3/8"-1"
- 0-40 bar
- 37-2,031 l/min.

Model SCG387

Function



- Brass/stainless
- 3/2 normally closed/open
- 3/8"-1"
- 0-40 bar
- 37-203 l/min.

Model G287/Namur

Function



- Brass/stainless
- 2/2 normally closed/open
- 3/8"-1"
- 0-40 bar
- 37-203 l/min.

Model G387/Namur

Function



- Brass/stainless
- 3/2 normally closed/open
- 3/8"-1"
- 0-40 bar
- 37-203 l/min.

For more information contact OEM Automatic, product area Pressure & Flow and order a separate catalogue.

TECHNICAL DATA

Connection	1/2 BSP
Differential air pressure max	40 bar
Differential oil pressure max	40 bar
Differential pressure min	0 bar
Differential water pressure max	40 bar
Flow max	86.6 l/min
Function 1	2/2
Function 2	Normally Closed (SPST)
Material body	Stainless steel
Temperature of media from	-20 °C
Temperature of media to	100 °C
Throughput	15 mm
Voltage AC	230 V