



## ASCO - COAXIAL VALVES

SCG287A013

- G3/8 - G1
- Temperature -20 to 100 ° C
- Pressure 0 to 40 bar
- Medium water, oil, gases
- Brass or stainless steel body



### PRODUCT DESCRIPTION

Coaxial valves are used in applications for high pressure and high flows. The coaxial valve can accommodate flow in both directions. Coaxial valves are available in electrically controlled versions and pressure controlled namur versions.

#### Model SCG287

#### Function



- Brass/stainless
- 2/2 normally closed/open
- 3/8"-1"
- 0-40 bar
- 37-2,031 l/min.

#### Model SCG387

#### Function



- Brass/stainless
- 3/2 normally closed/open
- 3/8"-1"
- 0-40 bar
- 37-203 l/min.

#### Model G287/Namur

#### Function



- Brass/stainless
- 2/2 normally closed/open
- 3/8"-1"
- 0-40 bar
- 37-203 l/min.

**Model G387/Namur**

**Function**



- Brass/stainless
- 3/2 normally closed/open
- 3/8"-1"
- 0-40 bar
- 37-203 l/min.

For more information contact OEM Automatic, product area Pressure & Flow and order a separate catalogue.

## TECHNICAL DATA

<b>Connection</b>	3/8 BSP
<b>Differential air pressure max</b>	40 bar
<b>Differential oil pressure max</b>	40 bar
<b>Differential pressure min</b>	0 bar
<b>Differential water pressure max</b>	40 bar
<b>Flow max</b>	36.6 l/min
<b>Function 1</b>	2/2
<b>Function 2</b>	Normally open (SPST)
<b>Material body</b>	Stainless steel
<b>Temperature of media from</b>	-20 °C
<b>Temperature of media to</b>	100 °C
<b>Throughput</b>	10 mm
<b>Voltage AC</b>	230 V