OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

VMK SERIES 2 WAY COAXIAL VALVE

Externally controlled

VMK
VMK series 2 way coaxial valve - Part numbers coming soon, contact us for more information



- Sizes DN 10 to DN 32
- Pressure range PN0 to 100 bar
- Maximum temperature +50°C
- ATEX available on request

PRODUCT DESCRIPTION

The VMK Series from Co-Ax Valves are 2/2 way (2 way) externally controlled coaxial valves with a threaded port connection. They are IP65 rated and suitable for media including gaseous, liquid, highly viscous and contaminated.

Orifice sizes available are DN 10 - DN 32, with a pressure range of PN 0 - 100 bar.

These coaxial valves are pressure balanced with spring return function of either normally open or normally closed.

Pneumatic actuation is via 5/2-way pilot valve and hydraulic actuation is via 4/2-way control valve.

The body materials are aluminium, brass, galvanized steel, nickel plated brass, nickel plated steel and stainless steel.

Seal materials available include NBR, PTFE, FPM, CR, EPDM and special materials.

Pilot valve interface is NAMUR / ISO 1 and normal voltage is DC 24 V / AC 230 V.

Options / accessories: Special threads, function NO, leak ports, flush ports, limit switches, manual overide, mounting, special voltage, connector M12x1, terminal box, explosion proof ATEX zone 1 and 2 category 3, pilot valve.

Please refer to the datasheet under 'downloads' for part numbers and/or technical data, we are working on getting all part numbers and technical data on the website as soon as possible.
;