

VS SERIES ELECTRIC ACTUATOR

Quarter Turn

VS300.90A.GF3
VS 300Nm 100-240VAC 3 POS

- IP68
- 100Nm to 300Nm
- Working temperature -20°C to +70°C
- Failsafe Actuator



PRODUCT DESCRIPTION

The VS is an IP68 rated Failsafe, quarter turn electric actuator, with aluminium housing and a cover made with polyamide (which meets UL94V0 standards) or aluminium (option). It comes with a manual override by external shaft or hand wheel, is available in torques of 100 Nm, 150 Nm and 300 Nm and is in accordance with CE-ROHS-REACH Directives. Available in Failsafe and Modulating/Positioning.

This model is now available with the Valpes Bluetooth Communication Module - enabling a secured connection and communication with the actuator(s) whether visible or not and even when concealed. A fantastic local control device option!

Part Numbers:

- VS100.90A.G00
- VS100.90B.G00
- VS150.90A.G00
- VS150.90B.G00
- VS300.90A.G00
- VS300.90B.G00
- VS100.909.R00
- VS150.909.R00
- VS300.909.R00
- VS100.90A.GS6
- VS100.90B.GS6
- VS150.90A.GS6
- VS150.90B.GS6
- VS300.90A.GS6
- VS300.90B.GS6
- VS100.90A.GP5
- VS100.90B.GP5
- VS150.90A.GP5
- VS150.90B.GP5
- VS300.90A.GP5
- VS300.90B.GP5
- VS100.90A.GF3
- VS100.90B.GF3
- VS150.90A.GF3
- VS150.90B.GF3
- VS300.90A.GF3
- VS300.90B.GF3
- VS100.90A.GPS

- VS100.90B.GPS
- VS150.90A.GPS
- VS150.90B.GPS
- VS300.90A.GPS
- VS300.90B.GPS
- VS100.90A.GFS
- VS100.90B.GFS
- VS150.90A.GFS
- VS150.90B.GFS
- VS300.90A.GFS
- VS300.90B.GFS

Please refer to the datasheet under 'downloads' for part numbers and/or technical data, we are working on getting all part numbers and technical data on the website as soon as possible.

;

TECHNICAL DATA

Connections	F07/F10
Operating Time (Seconds)	60 s
Power	45 W
Star Drive	22 F07/F10
Torque	300
Voltage	100-240 VAC, 100-350 VDC