

MINIMOTOR - DBSE BRUSHLESS SERVOMOTORS WITH PLANETARY GEARBOX

DBSE 55/50-5
 24/48V dc 600rpm 1.9 Nm

- Efficient and compact
- Saves individual cable runs
- Up to 95Nm
- Open Bus protocols
- Reduce machine build components



PRODUCT DESCRIPTION

MOTOR: Brushless 4-pole three-phase sinusoidal motor, totally enclosed. Rotor with NdFeB magnets. Thermal cutoff. Winding Class F. Thermal cutoff. Protection IP65 in compliance with IEC/EN 60529 standards. Bearings with reduced backlash and special grease for high temperatures.

DRIVE: Power 24 and/or 48 Vdc • Magnetic absolute encoder SSI (12bit single-turn / 20bit multi-turn) with internal buffer battery• 5 PNP digital inputs and 1 analogue input -10 +10V ext. (0-5 o 4-20mA optional) • 1 relay output (NC-NO) • USB port for parametrisation • Torque, speed, position and homing control.

GEAR UNIT: planetary with hardened steel case with broached precision teeth Class 7. Heat-treated sun and planet gears.

Seal rings in special high-temperature rubber (FKM).

Lubrication with special long-lasting oil.

Rated torque up to 95 Nm.

All the models are implemented with the new "open" platform, which permits configuration with the following primary protocols: CanOpen, Ethercat, Modbus, Ethernet/IP, Profinet, Powerlink.

For full motor specifications please see motor only 'DBS' or download literature below.

[Please click here for 2D and 3D drawings](#)

TECHNICAL DATA

4967_Rated current (A)	8A@24V/4.2A@48V
Ambient temperature	-10 ... +40°C
CanOpen	Yes
CE approved	Yes
Communication	USB
Communication error protection	Yes
Digital inputs	2 pnp (24Vdc, 500kHz) , 3 pnp (24Vdc, 7kHz)
Electronic brake output	24Vdc, max 0.5A



Electric motors



Geared motor



Worm gearmotors



Brushless servomotors



Clean products



Others

Please see product description above for 2D and 3D drawings