

CROUZET - BLDC GEARED MOTOR WITH INTEGRATED SMI21 DRIVE & CANOPEN NETWORK

802897XX SMI21 CANOPEN
Planetary 81mm gearmotor 141W 12-48Vdc 10-476rpm
120Nm max



- 12→48 V dc, 10→120 Nm, worm and planetary gears
- Speed, torque & position control. CANopen network
- Reduce control panel space & cabling
- Long life (>20,000 hours)
- IP65 as standard

PRODUCT DESCRIPTION

The SMI21 integrated drive is ideal for applications where speed, torque & positional control is required.

The motor also incorporates a high resolution 4096ppr incremental encoder ideal for precise positioning applications.

With CANopen communication the motor can be connected & controlled via the master CANopen control network.

The long lifetime of the brushless motor (>20,000 hours with rated load) means it is ideal for continuous or long duty applications.

Having the drive integrated into the motor can also save control panel space, reduce cabling and save set-up time.

3 motor sizes available with the same diameter (57mm x 57mm), with increasing motor lengths for more power/torque.

Planetary & worm gearbox options available for reducing the speed & increasing the output torque.

The motors are rated to IP65 dust/water protection class as standard.

Options for adaptation to the standard motor include adding a holding brake, special output shaft, special connectors, upgraded IP protection & special firmware developed according to your specific application requirements.

* Full documentation & user manuals available upon request.

TECHNICAL DATA

Diameter	81 mm
Integrated control	SMi21 CANopen
IP class	IP65
Life span	20,000h
Max. torque	120
Number of pulses per revolution	4096
Positioning feedback	Yes
Power	141 W
Ratio	i=5→236:1
Shaft diameter	19 mm
Speed options	10rpm→476rpm
Supply voltage	12 V DC, 24 V DC, 48 V DC
Type of gearbox	Planetary 1→3 stages

GEARBOXES FOR DcMind BRUSHLESS RANGE

4 to 120 Nm

- Planetary and worm gearboxes
- Shafts on ball bearings
- Long service life
- IP65



Part numbers

Gearbox	Dimensions Ø 32	Dimensions Ø 32	Dimensions Ø 31	Series
Type	E10495	E10496	E10497	E10410
Efficiency	0.8	0.76	0.7	0.6
Rated torque	4	12	25	60
Rated speed	1000	1000	1000	1000
Weight	0.7	0.8	1.1	1.6
Standard reduction ratios	6.75	20	30	100
Other ratios possible	13 - 150			

IP65 planetary gearbox: Metal gears on all stages. IP65 apart from the output shaft.
IP65 planetary gearbox: On the first stage, the planet gears are made of composite materials which improve efficiency and service life. On the other stages, the metal gears turn on needle bearings. IP65 apart from the output shaft.
IP65 planetary gearbox: All gears are metal and turn on needle bearings, resulting in excellent robustness and a very long service life. IP65 apart from the output shaft.

Worm gearbox: This gearbox combines a tempered steel worm and a hard bronze-halved gear wheel, thus ensuring a long service life. The wheel is coated with grease, ensuring an excellent slip coefficient and great heat dissipation. Output and bearings are used in combination with a compression spring to ensure a tight seal at the gearbox output shaft and the motor input shaft. IP65 gearbox.
 The casing is made of aluminum to minimize heat and provide with its supporting surface on the machine.
 However, due to the high power that can be transmitted by this gearbox and the low efficiency inherent in large worm gearbox reduction ratios, make sure that the gearbox casing temperature does not exceed 75°C during operation.
 The output shaft can be placed on the right or left, or can be a double shaft output on both sides.

GEARBOXES FOR DcMind BRUSHLESS RANGE

4 to 120 Nm

- Planetary and worm gearboxes
- Shafts on ball bearings
- Long service life
- IP65



Part numbers

Gearbox	Dimensions Ø 32	Dimensions Ø 32	Dimensions Ø 31	Series
Type	E10495	E10496	E10497	E10410
Efficiency	0.8	0.76	0.7	0.6
Rated torque	4	12	25	60
Rated speed	1000	1000	1000	1000
Weight	0.7	0.8	1.1	1.6
Standard reduction ratios	6.75	20	30	100
Other ratios possible	13 - 150			

IP65 planetary gearbox: Metal gears on all stages. IP65 apart from the output shaft.
IP65 planetary gearbox: On the first stage, the planet gears are made of composite materials which improve efficiency and service life. On the other stages, the metal gears turn on needle bearings. IP65 apart from the output shaft.
IP65 planetary gearbox: All gears are metal and turn on needle bearings, resulting in excellent robustness and a very long service life. IP65 apart from the output shaft.

Worm gearbox: This gearbox combines a tempered steel worm and a hard bronze-halved gear wheel, thus ensuring a long service life. The wheel is coated with grease, ensuring an excellent slip coefficient and great heat dissipation. Output and bearings are used in combination with a compression spring to ensure a tight seal at the gearbox output shaft and the motor input shaft. IP65 gearbox.
 The casing is made of aluminum to minimize heat and provide with its supporting surface on the machine.
 However, due to the high power that can be transmitted by this gearbox and the low efficiency inherent in large worm gearbox reduction ratios, make sure that the gearbox casing temperature does not exceed 75°C during operation.
 The output shaft can be placed on the right or left, or can be a double shaft output on both sides.