

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk




PANEL MOUNT FEED-THROUGH TERMINALS SDK 4-16 MM²

SDK Series

17453.6 SDK 16-AP/6, 6-pole Adaptor plate for SDK 16

- 32A to 57A, 250V-1000V
- Polyamide 6.6 UL94-V0
- Easy to align side-by-side
- · Secure and robust mounting
- · Custom colours available



PRODUCT DESCRIPTION

The SDK series is a panel feed-through terminal system designed for use in a wide range of applications including electrical device and enclosure technologies.

This range of terminals provide a flexible modular-based system where a more robust and secure connection is required.

The wide range of system components can be combined to achieve various voltages - with a maximum voltage level of 1000 V (UL 600 V) even at Contamination degree 3.

The insulated housing is made of polyamide 6.6 UL 94 V-0. The pegs can be used to link the housings together to form multi-pole units. Optional additional flange plates are available for further improved mechanical stability.

The standard range of PMC SB or PMC BSTR marker tags can be used to label the feed-though terminals.

Additional informationadapter plate outside 6pcs stripColourGreyCountry of originDEFlammability classUL94-V0MaterialPolyamide 6.6Operating temperature from-40 °COperating temperature to120 °CPack size10Tariff code85369010Weight3.9 g	Colour Grey	
Flammability class UL94-V0 Material Polyamide 6.6 Operating temperature from 120 °C Pack size 10 Tariff code	·	
Flammability class Material Operating temperature from -40 °C Operating temperature to 120 °C Pack size 10 Tariff code 85369010	Country of origin	
MaterialPolyamide 6.6Operating temperature from-40 °COperating temperature to120 °CPack size10Tariff code85369010	DE	
Operating temperature from -40 °C Operating temperature to 120 °C Pack size 10 Tariff code 85369010	Flammability class UL94-V0	
Operating temperature to120 °CPack size10Tariff code85369010	Material Polyamide 6.6	
Pack size 10 Tariff code 85369010	Operating temperature from -40 °C	
Tariff code 85369010	Operating temperature to 120 °C	
	Pack size 10	
Weight 3.9 g	Tariff code 85369010	
• • •		