

ADVANTECH FPM-7061T MONITOR

FPM-7061T-R3AE

6.5" VGA Industrial Monitor, Touchscreen, Direct-VGA/DP

- 5-wire analog resistive touch
- SECC Chassis with IP66 in front
- 4:3 format
- 6,5"



PRODUCT DESCRIPTION

The FPM-7000 Series is the most robust and industry-class screen in our range. With a full-length glass on the front, this monitor becomes IP66 classed and robust, which means that the frame does not feel and creates a significantly better overall impression than other series and models on the market.

With viewing angles and high brightness, this monitor is suitable for all types of applications

TECHNICAL DATA

| | |
|-----------------------|------------------------|
| Approvals | CCC, CE, FCC, UL, BSMI |
| Backlight | LED LCD |
| Contrast | 600:1 |
| Depth | 46.1 mm |
| Display format | 4:3 |
| Display resolution | 640x480 |
| Display size | 6.5 |
| Front panel thickness | 7 mm |
| Height | 152 mm |
| Hole size | 189,1x142,1 |
| IP class | IP66 |
| Luminance | 800 cd/m ² |
| Material front frame | Aluminium |
| Material protection | Zinc plated steel |

| | |
|-----------------------------|---------|
| Number of display colours | 16.2 |
| Power consumption | 10 W |
| Power supply | 24 V DC |
| Storage temperature max | 70 °C |
| Storage temperature min | -30 °C |
| Temperature operational max | 60 °C |
| Temperature operational min | -20 °C |
| Weight | 1.2 kg |
| Width | 199 mm |
| Viewing angle | 160/140 |