

## IDEM - MULTIFUNCTIONAL UGB-KLTM ACCESS DEVICE

525001  
 UGB2-KLTM-RFID - Manual Override



- Locking force F1Max = 3000N
- PL e Cat. 4
- An escape option
- Version for 2 or 4 buttons (lights, switches, e-stop)
- Built-in KLTM circuit breaker with RFID coding

### PRODUCT DESCRIPTION

UGB-KLTM is a multifunctional device that provides integrated protection and comprehensive access control. The product is intended for applications in which the operator has full access to a dangerous zone.

The switch is available in a cast metal version. In addition, the switch can have 2 or 4 buttons (lamps, switches) that can be freely configured. The UGB-KLTM multifunctional access device is coded with RFID, which ensures the highest level of interference immunity in accordance with the requirements of ISO14119.

### TECHNICAL DATA

<b>Approvals</b>	ISO 13849-1, ISO 14119, EN60204-1, EN62061, EN60947-5-1, UL 508
<b>Conduit entry</b>	M20
<b>Head material</b>	Stainless steel 316
<b>Holding force (F1Max)</b>	3000 N
<b>Housing material</b>	Die cast metal
<b>Integrated LED indication</b>	Yes
<b>IP class</b>	IP65
<b>Maximum approach / withdrawal speed</b>	600 mm/s
<b>Mounting</b>	4 x M5
<b>Operating temperature</b>	-25°C ... +40°C
<b>PFHd</b>	4,77 x 10 <sup>-10</sup>
<b>PL</b>	e
<b>Rated insulation voltage</b>	600 V AC
<b>SIL</b>	3
<b>Solenoid Voltage</b>	24V dc
<b>Travel for positive opening</b>	10 mm
<b>Weight</b>	1980 g
<b>Withstand voltage</b>	2500 V AC

