

## T22CT AC TRANSDUCER

T22CT1AA75L000000

AC Transducer 70x30mm 50a/4-20mA 24VDC

- Measurement of AC current for frequency 50/60Hz
- Provides proportional 4...20 mA or 0...20mA DC output
- High electric isolation between primary conductor and output
- Direct mounting onto the bus bar by means of integrated fixing screws



### PRODUCT DESCRIPTION

T22CT a transducer for measurement of AC current. It provides 4 to 20 mA or 0 to 20mA DC output. It can be used for:

- For network analysis, monitoring
- Measuring of non -sinusoidal and distorted networks.

Features:

- Measurement of AC current for frequency 50/60Hz
- Provides proportional 4 - 20 mA or 0-20 mA DC output.
- High electric isolation between primary conductor and output.
- Easy and safety electrical connection by means of spring clamp terminal.
- Direct mounting onto the bus bar by means of integrated fixing screws which are part of the unit.
- Mounting onto 35 mm DIN rail by means of optional supply of snap on mounting.

### TECHNICAL DATA

<b>Electrical connection</b>	70x30mm
<b>Input type</b>	50A
<b>IP class</b>	IP20
<b>Output</b>	4..20mA
<b>Supply voltage</b>	24Vdc
<b>Weight</b>	0.5 kg