

CHROME MODULAR POWER SUPPLY 5VDC

5VDC, 1.5A, 7W

DRC-5V10W1AZ
Power Supply Chrome 5VDC 7.5W 1.5A

- Width 18 mm
- Efficiency >78%
- NEC Class 2
- Din rail mount



PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Input voltage ac	100-240 V
Input voltage ac min	90 V AC
Input voltage ac max	264 V AC
Input voltage dc	125-375 V
Input voltage dc min	125 V DC
Input voltage dc max	375 V DC
Inrush current at 120 V ac typical	15 A
Inrush current at 230 V ac typical	30 A

OUTPUT DATA

Output voltage	5 V DC
Output voltage min	4.75 V DC
Output voltage max	5.25 V DC
Output current	1.5 A
Power	7.5 W

EFFICIENCY / LIFETIME / MTBF

Efficiency	78 %
------------	------

DIMENSIONS

Width	18 mm
Height	91 mm
Depth	55.6 mm
Weight	0.06 kg

OTHER

Approvals	CB, CE, NEC Class 2, TÜV, UL
Hold time at 120 V ac, typical full load	10 ms
Hold time at 230 V ac, typical full load	60 ms
IP class	IP20
Clamp type	Screw
Material protection	Plastic
Supply frequency	50-60 Hz
Power consumption 120 V ac	0.3 A
Power consumption 230 V ac	0.2 A
Temperature min without derating	-25 °C
Temperature max without derating	55 °C

