OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CHROME MODULAR POWER SUPPLY 5VDC

5VDC, 1.5A, 7W

DRC-5V10W1AZ
Power Supply Chrome 5VDC 7.5W 1.5A



- Width 18 mm
- Efficiency >78%
- NEC Class 2
- Din rail mount

PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Input voltage ac	100-240 V
Input voltage ac min	90 V AC
Input voltage ac max	264 V AC
Input voltage dc	125-375 V
Input voltage dc min	125 V DC
Input voltage dc max	375 V DC
Inrush current at 120 V ac typical	15 A
Inrush current at 230 V ac typical	30 A

OUTPUT DATA

Output voltage	5 V DC
Output voltage min	475 V DC
Output voltage max	525 V DC
Output current	15 A
Power	75 W

EFFICIENCY / LIFETIME / MTBF

Efficiency	78 %

DIMENSIONS

Width	18 mm
Height	91 mm
Depth	556 mm
Weight	6 kg

OTHER

Approvals	CB, CE, NEC Class 2, TÜV, UL
Hold time at 120 V ac, typical full load	10 ms
Hold time at 230 V ac, typical full load	60 ms
IP class	IP20
Clamp type	Screw
Material protection	Plastic
Supply frequency	50-60 Hz
Power consumption 120 V ac	3 A
Power consumption 230 V ac	2 A
Temperature min without derating	-25 °C
Temperature max without derating	55 °C

