

POWER SUPPLY 3-PHASE, 72 V DC DIMENSION X SERIES

XT40.722

PSU 3PH 480V ac I/P 72V dc 13.3A 960W O/P

- Output current of 13 A
- 95.5% efficiency
- 96 mm wide
- 25% power boost
- Very high short-circuit current



PRODUCT DESCRIPTION

The power supplies in the Dimension X-Series include a new and innovative concept for generating an isolated dc voltage from a three-phase mains system. A semi-regulated resonant converter enables a very compact design, maximum efficiency and extremely competitive pricing with only a small compromise in the output voltage regulation, output ripple and hold-up time.


Weighing just 1.4 kg, the device provides 960 watts of continuous output power and an additional 25% power reserve for dynamic loads. The light-weight design along with compact dimensions facilitate straightforward mounting on DIN-rail.

Primary use are applications involving supplies to motors, valves and other load circuits with a high power consumption, where an accurate output voltage regulation which is standard on traditional switched-mode power supplies is not required.


Furthermore, these switched-mode power supplies can often replace mains transformers with rectifiers.

We recommend free space of 40 mm above and 20 mm under the unit, and 5 mm at the sides. (If adjacent components are considered as heat sources, a distance of 15 mm is recommended.)

Input voltage range



Output characteristics



TECHNICAL DATA

INPUT DATA

Input voltage ac	480 V
Input voltage ac min	432 V AC
Input voltage ac max	528 V AC

Inrush current at 400 V ac typical	4 A
Power factor at 400 V ac, full load. Typical	0.93
Number of phases	3

OUTPUT DATA

Output voltage	72 V DC
Output voltage min	72 V DC
Output voltage max	72 V DC
Output current	13.3 A
Power	960 W

EFFICIENCY / LIFETIME / MTBF

Efficiency at 400 V ac, full load, typical	95.5 %
MTBF (IEC 61709) 400 V ac, max loan, +40 °C	539000 h

DIMENSIONS

Width	96 mm
Height	124 mm
Depth	159 mm
Weight	1.4 kg

OTHER

Approvals	CB, CE, CSA, UL
Hold time at 400 V ac, typical full load	3 ms
IP class	IP20
Material protection	Aluminium
Supply frequency	50-60 ±6 %
Ripple max	200 mV pp
Series	Dimension X
Power consumption at 400 V ac	1.4 A
Power drop from +60 °C to + 70 °C	24 W/°C
Temperature min without derating	-25 °C
Temperature max without derating	60 °C
Type Power Supply	AC-DC
Active Transient	Yes




Fig. 9-1 Efficiency vs. output current




Fig. 9-2 Losses vs. output current





Fig. 5-1 Output voltage vs. input voltage and input current

Fig. 15-1 Output current vs. ambient temp.,



25. COMPARISON BETWEEN THE XT40, A TRANSFORMER AND A TRADITIONAL SWITCHED-MODE POWER SUPPLY

	XT40 Semi-regulated power supply	Traditional switched-mode power supply	Transformer power supply
Input voltage range	+	++	-
Inrush current surge	++	+	-
Hold-up time	-	+	-
Phase-loss operation	-	+	-
Efficiency	+++	++	-
Output voltage regulation	+	++	-
Output adjustment range	-	++	-
Supply & noise voltage	-	++	-
Error diagnostics	++	++	-
Harmonic distortion (THD)	+	+	-
EMC	++	++	+
Size of installation	++	++	-
Size	+++	++	-
Weight	+++	+	-

+++...very, very good ++...very good +...good -...poor




Fig. 11-4 Front side of XT40.721

Fig. 22-1 Front view




Fig. 22-2 Side view





Fig. 5-1 Output voltage vs. input voltage and input current




Fig. 15-1 Output current vs. ambient temp.,




Fig. 9-1 Efficiency vs. output current





Fig. 9-2 Losses vs. output current



25. COMPARISON BETWEEN THE XT40, A TRANSFORMER AND A TRADITIONAL SWITCHED-MODE POWER SUPPLY

	XT40 Semi-regulated power supply	Traditional switched-mode power supply	Transformer power supply
Input voltage range	+	++	-
Inrush current surge	++	+	-
Hold-up time	-	+	-
Phase-loss operation	-	+	-
Efficiency	+++	++	-
Output voltage regulation	+	++	-
Output adjustment range	-	++	-
Ripple & noise voltage	-	++	-
Error diagnostics	++	++	-
Harmonic distortion (THD)	+	+	-
EMC	++	++	+
Ease of installation	++	++	-
Size	+++	++	-
Weight	+++	+	-

+++ : very, very good ++ : very good + : good - : poor



Fig. 22-1 Front view




Fig. 22-2 Side view

