

CHROME II MODULAR POWER SUPPLY 24VDC

DRC-24V015W1RZ
 PSU Chrome II 100-240VAC/24VDC, 15W/0,63A

- Universal AC Input Range and DC Input Supported
- Mechanical dimension designs to meet DIN 43880 for building automation
- Class II, Double Isolation (No Earth connection is required)
- Low no load power consumption & meet with DOE VI
- NEC Class 2 / Limited Power Source (LPS) certified



PRODUCT DESCRIPTION

TECHNICAL DATA

INPUT DATA

Input voltage ac	100-240 V
Input voltage ac min	85 V AC
Input voltage ac max	264 V AC
Input voltage dc	125-375 V
Input voltage dc min	125 V DC
Input voltage dc max	375 V DC
Inrush current at 230 V ac typical	40 A

OUTPUT DATA

Output voltage	24 V DC
Output voltage min	21.6 V DC
Output voltage max	26.4 V DC
Output current	0.63 A
Power	15 W

EFFICIENCY / LIFETIME / MTBF

Efficiency	87.5 %
-------------------	--------

DIMENSIONS

Width	18 mm
Height	87.5 mm
Depth	55 mm
Weight	0.06 kg

OTHER

Approvals	BSMI, CB, CCC, CE, NEC Class 2, REACH, RoHS, TÜV, UL
Hold time at 120 V ac, typical full load	18 ms
Hold time at 230 V ac, typical full load	79 ms
IP class	IP20
Clamp type	Screw
Material protection	Plastic
Supply frequency	50-60 Hz
Power consumption 120 V ac	0.5 A
Power consumption 230 V ac	0.3 A
Temperature min without derating	-40 °C
Temperature max without derating	70 °C

