

IDEM GLHD WIRE SWITCH

141040-FZ

GLHD ½NPT '4NC 2NO' E stop - -40°



- Up to 200 m for one switch
- 4 NC + 2 NO contacts
- 2 - color LED
- Integrated emergency button
- Available in the EX version



PRODUCT DESCRIPTION

GLHD wire switch in an aluminum alloy housing, was created to protect long conveyors, with a range of up to 200 m per one switch. The 2-color LED, signaling the operation of the switch, is visible from a large distance. This switch, combined with the GLHL and GLHR models, provides a range of up to 250 m per one set.

The GLHD wire switches are equipped with 4 NC contacts and 2 NO contacts.

TECHNICAL DATA

Annual usage	8 cycles per hour/24 hours per day/365 days
Approvals	EN60947-5-5, ISO 13850, ISO 13849-1, EN62061, EN60947-5-1, UL 508, CE, cULus, TÜV
Conduit entry	4 x 1/2" NPT
Contact type	EN60947-5-1 double break type Zb. Snap action up to 4NC (positive break) 2NO (auxiliary)
Contacts	4NC 2NO
Fittings	E-stop
Housing material	Die cast metal
Integrated emergency stop button	Yes
Integrated LED indication	No
IP class	IP67
Material contacts	Silver
Mechanical reliability B10d	1.5 x 10 ⁶ operations at 100mA load

