



## IDEM ROPE PULL SWITCH GLHL-SS & GLHR-SS STAINLESS STEEL

145005-AS

GLHL-SS M20 '4NC 2NO' E Stop &amp; Steady LED 24V

- Up to 100 m per switch
- 4 NC contacts + 2 NO contacts
- Dual colour LED
- Integrated emergency stop button
- ATEX Version available



### PRODUCT DESCRIPTION

The GLHR/L-SS is a robust heavy duty safety rope pull switch and is designed to protect long conveyor lengths up to 125m (2 switches) or up to 100m using a single switch.

The stainless steel 316 housings are designed specifically to withstand the tough environments found in the food and pharmaceutical industries.

They will survive chemical and detergent washdown by providing all stainless steel parts and robust IP67 and IP69K sealing by using integral bellows and gaskets.

They can be used to complement the GLHD-SS (dual head) versions at each end of the rope.

### TECHNICAL DATA

|                                  |  |
|----------------------------------|--|
| Annual usage                     | 8 cycles per hour/24 hours per day/365 days  |
| Approvals                        | EN60947-5-5, ISO 13850, ISO 13849-1, EN62061, EN60947-5-1, CE, cULus, TÜV, UL 508        |
| Conduit entry                    | 4 x M20  |
| Contact type                     | EN60947-5-1 double break type Zb, Snap action up to 4NC (positive break) 2NO (auxiliary) |
| Contacts                         | 4NC 2NO  |
| Fittings                         | E-stop and LED   |
| Housing material                 | Stainless steel 316  |
| Integrated emergency stop button | Yes  |
| Integrated LED indication        | Yes  |



