

## IDEM STAINLESS STEEL WIRE SWITCH GLM-SS

148061  
GLM-SS ½NPT '4NC' E Stop

- Up to 30 m on one switch
- 5 different contact configurations
- 2 - color LED
- Integrated emergency button



### PRODUCT DESCRIPTION

The GLM-SS wire switches in a stainless steel housing have been created as a high-quality system for securing short conveyors, with a range of up to 30 m per one switch. Using two switches, the range is increased to 50 m. They are suitable for conveyor systems operating in difficult environments. Ideally suited for use in the food processing industry.

The 2-color LED, signaling the operation of the switch, is visible from a large distance. The GLM-SS wire switch has 5 different contact configurations.

### TECHNICAL DATA

Annual usage	8 cycles per hour/24 hours per day/365 days
Approvals	EN60947-5-5, ISO 13850, ISO 13849-1, EN62061, EN60947-5-1, UL 508, CE, cULus, TÜV
Conduit entry	3 x 1/2" NPT
Contact type	EN60947-5-1 double break type Zb. Snap action up to 4NC (positive break) 2NO (auxiliary)
Contacts	4NC
Fittings	E-stop
Housing material	Stainless steel 316
Integrated emergency stop button	Yes
Integrated LED indication	No
IP class	IP69K
Mechanical reliability B10d	1.5 x 10 <sup>6</sup> operations at 100mA load
Mounting	4 x M5

<b>MTTFd</b>	214 years
<b>Operating temperature</b>	-25°C +80°C
<b>PFHd</b>	$<1.0 \times 10^{-7}$
<b>Rope span</b>	Up to 50m (2 switches) 30m (1 switch)
<b>Rope tension device</b>	IDEM tensioner/gripper (quick fixing)
<b>Rope type</b>	4.00mm outside diameter. Steel inner - PVC sheath
<b>Short circuit overload protection</b>	Fuse externally 10A(FF)
<b>Tension force (typical mid setting)</b>	130 N
<b>Termination</b>	Clamp up to 2.5mm <sup>2</sup> conductors
<b>Thermal current (Ith)</b>	10 A
<b>Typical operating force (rope pulled)</b>	<125N <300mm deflection
<b>Weight</b>	640 g

