

ABS ENCLOSURES

48100

KEM 310 M2ABS, ABS Enclosure, 3-Pole, 10A



- 10-630A switch ratings
- Other switch configurations available
- Recommended for indoor installation only
- Tested to IEC 60947-3



PRODUCT DESCRIPTION

Switch Disconnectors housed in high-quality ABS enclosures.

All ABS enclosures are IP65 rated at a minimum for robust protection against dust and water.

Available in both black/grey and yellow/red.

These enclosures are made from recyclable ABS plastic which provides excellent insulating properties and good resistance against many chemicals.

Tested to IEC 60947-3.

Note! Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector.

TECHNICAL DATA

GENERAL DATA

Number of poles	3
Rated insulation voltage Ui	800 V
Rated thermal current, Ith	20 A
Enclosure dimensions	130x96x106mm
Terminals / Bolt size Cu	1.5-16
Nominal values with cable size	2.5
Weight	0,4 kg

RATED OPERATIONAL CURRENT, IE

Operational current - AC-21A - 400/415V	20 A
Operational current - AC-21A - 500V	20 A

Operational current - AC-21A - 690V	20 A
Operational current - AC-22A - 400/415V	10 A
Operational current - AC-22A - 500V	10 A
Operational current - AC-22A - 690V	10 A
Operational current - AC-23A - 400/415V	10 A
Operational current - AC-23A - 500V	10 A
Operational current - AC-23A - 690V	10 A

RATED OPERATIONAL POWER FOR 3-PHASE (1500 R.P.M.) SQUIRREL CAGE INDUCTION MOTORS (KW)

Operational power - AC-23A - 400/415V	5,5 kW
Operational power - AC-23A - 500V	5,5 kW
Operational power - AC-23A - 690V	7,5 kW

RATED FUSED SHORT CIRCUIT CURRENT

Back-up fuse	63 A
R.M.S value, IK	50
Peak value	7,2 kA
Rated impulse withstand voltage Uimp	8 kV
Rated short circuit making capacity at 690V, Icm	2.5
Rated short time withstand current at 690V (1 s), Icw	1.7

RATED BREAKING CAPACITY, ICN

Breaking capacity - AC-23A - 400/415V	80 A
Breaking capacity - AC-23A - 500V	80 A
Breaking capacity - AC-23A - 690V	80 A

ADDITIONAL DETAILS

Electrical endurance	3000 operations
Mechanical endurance	50000 operations
Max terminal torque	1.8
Tariff code	85365080
Country of origin	FI
Switch colour	Black/grey

