

PAINTED STEEL ENCLOSURES

33840

KET 31250T T10A, Sheet Steel Enclosure, 3-Pole,
1250A

- 16-1600A switch ratings
- Other switch configurations available
- Excellent insulating properties
- Tested to IEC 60947-3



PRODUCT DESCRIPTION

Switch Disconnectors housed in high-quality sheet steel enclosures.

All sheet steel enclosures are IP66 rated at a minimum for robust protection against dust and water.

Available in both black/grey and yellow/red.

Tested to IEC 60947-3.

Note! Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector.

TECHNICAL DATA

GENERAL DATA

Number of poles	3
Rated insulation voltage U_i	1000 V
Rated thermal current, I_{th}	1250 A
Enclosure dimensions	1200x600x300mm
Terminals / Bolt size Cu	6-70
Weight	75 kg

RATED FUSED SHORT CIRCUIT CURRENT

Rated impulse withstand voltage U_{imp}	8 kV
---	------

ADDITIONAL DETAILS

Electrical endurance	2000 operations
----------------------	-----------------

Mechanical endurance	10000 operations
Tariff code	85365080
Country of origin	FI
Switch colour	Black/grey

