OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

PAINTED STEEL ENCLOSURES

33842
KET 31600T T10A, Sheet Steel Enclosure, 3-Pole, 1600A



- 16-1600A switch ratings
- Other switch configurations available
- Excellent insulating properties
- Tested to IEC 60947-3

PRODUCT DESCRIPTION

Switch Disconnectors housed in high-quality sheet steel enclosures.
All sheet steel enclosures are IP66 rated at a minimum for robust protection against dust and water.
Available in both black/grey and yellow/red.

Tested to IEC 60947-3.
Note! Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector.

TECHNICAL DATA

GENERAL DATA

Number of poles	3
Rated insulation voltage Ui	1000 V
Rated thermal current, Ith	1600 A
Enclosure dimensions	1200x600x300mm
Terminals / Bolt size Cu	6-70
Weight	85 kg

RATED FUSED SHORT CIRCUIT CURRENT

Rated impulse withstand voltage Uimp	8 kV

ADDITIONAL DETAILS

Electrical endurance	2000 operations
Mechanical endurance	10000 operations

Tariff code	85365080
Country of origin	FI

Switch colour	Black/grey

