

## PAINTED STEEL ENCLOSURES

33938

KET 41250 T10A, Sheet Steel Enclosure, 4-Pole,  
1250A

- 16-1600A switch ratings
- Other switch configurations available
- Excellent insulating properties
- Tested to IEC 60947-3



### PRODUCT DESCRIPTION

Switch Disconnectors housed in high-quality sheet steel enclosures.

All sheet steel enclosures are IP66 rated at a minimum for robust protection against dust and water.

Available in both black/grey and yellow/red.

Tested to IEC 60947-3.

Note! Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector.

## TECHNICAL DATA

### GENERAL DATA

Number of poles	4
Rated insulation voltage $U_i$	1000 V
Rated thermal current, $I_{th}$	1250 A
Enclosure dimensions	1200x600x300mm
Terminals / Bolt size Cu	6-70
Weight	77 kg

### RATED FUSED SHORT CIRCUIT CURRENT

Rated impulse withstand voltage $U_{imp}$	8 kV
---	------

### ADDITIONAL DETAILS

Electrical endurance	2000 operations
----------------------	-----------------

Mechanical endurance	10000 operations
Tariff code	85365080
Country of origin	FI
Switch colour	Black/grey

