

PAINTED STEEL ENCLOSURES

34169

KET 4250 YR T6, Sheet Steel Enclosure, Yellow/Red,
4-Pole, 250A

- 16-1600A switch ratings
- Other switch configurations available
- Excellent insulating properties
- Tested to IEC 60947-3



PRODUCT DESCRIPTION

Switch Disconnectors housed in high-quality sheet steel enclosures.

All sheet steel enclosures are IP66 rated at a minimum for robust protection against dust and water.

Available in both black/grey and yellow/red.

Tested to IEC 60947-3.

Note! Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector.

TECHNICAL DATA

GENERAL DATA

Number of poles	4
Rated insulation voltage Ui	1000 V
Rated thermal current, Ith	315 A
Enclosure dimensions	600x400x200mm
Terminals / Bolt size Cu	M10
Nominal values with cable size	120
Weight	20 kg

RATED OPERATIONAL CURRENT, IE

Operational current - AC-21A - 400/415V	250 A
Operational current - AC-21A - 500V	250 A

Operational current - AC-21A - 690V	250 A
Operational current - AC-22A - 400/415V	250 A
Operational current - AC-22A - 500V	250 A
Operational current - AC-22A - 690V	250 A
Operational current - AC-23A - 400/415V	250 A
Operational current - AC-23A - 500V	250 A
Operational current - AC-23A - 690V	250 A
Operational current - AC-23A - 1000V	135 A

RATED OPERATIONAL POWER FOR 3-PHASE (1500 R.P.M.) SQUIRREL CAGE INDUCTION MOTORS (KW)

Operational power - AC-23A - 400/415V	132 kW
Operational power - AC-23A - 500V	160 kW
Operational power - AC-23A - 690V	250 kW

RATED FUSED SHORT CIRCUIT CURRENT

Back-up fuse	250 A
R.M.S value, IK	100
Peak value	26 kA
Rated impulse withstand voltage Uimp	8 kV
Rated short circuit making capacity at 690V, Icm	14
Rated short time withstand current at 690V (1 s), Icw	8

RATED BREAKING CAPACITY, ICN

Breaking capacity - AC-23A - 400/415V	2000 A
Breaking capacity - AC-23A - 500V	2000 A
Breaking capacity - AC-23A - 690V	2000 A

ADDITIONAL DETAILS

Electrical endurance	2000 operations
Mechanical endurance	16000 operations
Max terminal torque	15-22
Tariff code	85365080
Country of origin	FI
Switch colour	Red/yellow

