

## PAINTED STEEL ENCLOSURES

33835

KET 4630 YR T7, Sheet Steel Enclosure, Yellow/Red,  
4-Pole, 630A

- 16-1600A switch ratings
- Other switch configurations available
- Excellent insulating properties
- Tested to IEC 60947-3



### PRODUCT DESCRIPTION

Switch Disconnectors housed in high-quality sheet steel enclosures.

All sheet steel enclosures are IP66 rated at a minimum for robust protection against dust and water.

Available in both black/grey and yellow/red.

Tested to IEC 60947-3.

Note! Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector.

## TECHNICAL DATA

### GENERAL DATA

Number of poles	4
Rated insulation voltage $U_i$	1000 V
Rated thermal current, $I_{th}$	630 A
Enclosure dimensions	800x600x250mm
Terminals / Bolt size Cu	M12
Nominal values with cable size	2x185
Weight	40 kg

### RATED OPERATIONAL CURRENT, $I_E$

Operational current - AC-21A - 400/415V	630 A
Operational current - AC-21A - 500V	630 A

Operational current - AC-21A - 690V	630 A
Operational current - AC-22A - 400/415V	630 A
Operational current - AC-22A - 500V	630 A
Operational current - AC-22A - 690V	630 A
Operational current - AC-23A - 400/415V	630 A
Operational current - AC-23A - 500V	630 A
Operational current - AC-23A - 690V	630 A

## RATED OPERATIONAL POWER FOR 3-PHASE (1500 R.P.M.) SQUIRREL CAGE INDUCTION MOTORS (KW)

Operational power - AC-23A - 400/415V	355 kW
Operational power - AC-23A - 500V	400 kW
Operational power - AC-23A - 690V	630 kW

## RATED FUSED SHORT CIRCUIT CURRENT

Back-up fuse	630 A
R.M.S value, IK	100
Peak value	76 kA
Rated impulse withstand voltage Uimp	8 kV
Rated short circuit making capacity at 690V, Icm	60
Rated short time withstand current at 690V (1 s), Icw	28

## RATED BREAKING CAPACITY, ICN

Breaking capacity - AC-23A - 400/415V	5040 A
Breaking capacity - AC-23A - 500V	5040 A
Breaking capacity - AC-23A - 690V	5040 A

## ADDITIONAL DETAILS

Electrical endurance	2000 operations
Mechanical endurance	10000 operations
Max terminal torque	50-75
Tariff code	85365080
Country of origin	FI
Switch colour	Red/yellow

