

STAINLESS STEEL ENCLOSURES

34371

KER 4160 YR RA5, Stainless Steel Enclosure,
Yellow/Red, 4-Pole, 160A

- 16-1600A switch ratings
- Other switch configurations available
- Hygienic and corrosion resistant
- Tested to IEC 60947-3



PRODUCT DESCRIPTION

Switch Disconnectors housed in high-quality stainless steel enclosures.

All stainless steel enclosures are IP66 rated at a minimum for robust protection against dust and water.

Available in both black/grey and yellow/red.

Stainless steel is ideal for applications where hygiene and good protection against corrosion are important.

These enclosures are also available with EMC and EMC/EX protection upon request.

Tested to IEC 60947-3.

Note! AI-cables cannot be connected directly to switch terminals. For AI-cable connection please use a bi-metal cable connector.

TECHNICAL DATA

GENERAL DATA

Number of poles	4
Rated insulation voltage Ui	800 V
Rated thermal current, Ith	200 A
Enclosure dimensions	400x300x120mm
Terminals / Bolt size Cu	6-70
Nominal values with cable size	95
Weight	7 kg

RATED OPERATIONAL CURRENT, IE

Operational current - AC-21A - 400/415V	160 A
Operational current - AC-21A - 500V	160 A

Operational current - AC-21A - 690V	160 A
Operational current - AC-22A - 400/415V	160 A
Operational current - AC-22A - 500V	160 A
Operational current - AC-22A - 690V	160 A
Operational current - AC-23A - 400/415V	160 A
Operational current - AC-23A - 500V	100 A
Operational current - AC-23A - 690V	100 A

RATED OPERATIONAL POWER FOR 3-PHASE (1500 R.P.M.) SQUIRREL CAGE INDUCTION MOTORS (KW)

Operational power - AC-23A - 400/415V	90 kW
Operational power - AC-23A - 500V	55 kW
Operational power - AC-23A - 690V	90 kW

RATED FUSED SHORT CIRCUIT CURRENT

Back-up fuse	160 A
R.M.S value, IK	65
Peak value	15 kA
Rated impulse withstand voltage Uimp	8 kV
Rated short circuit making capacity at 690V, Icm	8
Rated short time withstand current at 690V (1 s), Icw	5

RATED BREAKING CAPACITY, ICN

Breaking capacity - AC-23A - 400/415V	1280 A
Breaking capacity - AC-23A - 500V	800 A
Breaking capacity - AC-23A - 690V	800 A

ADDITIONAL DETAILS

Electrical endurance	2000 operations
Mechanical endurance	16000 operations
Max terminal torque	6
Tariff code	85365080
Country of origin	FI
Switch colour	Red/yellow

