

630-800A SWITCH DISCONNECTORS

48400

KU 3800 SV, Screw Mounted, 3-Pole, 800A

- Made of halogen free thermoplastics with 100% recyclability
- Auxilliary contacts available
- Terminal covers and phase barriers available
- Icw 690V (1s) 28kA



PRODUCT DESCRIPTION

Katko 630-800A switch disconnectors are a reliable switch for demanding industrial applications. They are made of halogen free thermoplastics which are 100% recyclable.

Available with a direct handle, or seperate LKX150 handle and LVK228 shaft.
Yellow/Red handles and shaft of different length available upon request.

Option for test position for testing auxilliary contacts while main contacts remain open. Note, only available on request.
Auxiliary contacts available (1.V160KU or 2.V160KU), up to 8 NC / 8 NO. Terminal covers and phase barriers (VS800) available.
Note! Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector.

TECHNICAL DATA

GENERAL DATA

Number of poles	3
Rated insulation voltage Ui	1000 V
Rated thermal current, Ith	800 A
Type	Screw-mounted
Terminals / Bolt size Cu	M12
Nominal values with cable size	2x240
Weight	4.55 kg

RATED OPERATIONAL CURRENT, IE

Operational current - AC-21A - 400/415V	800 A
Operational current - AC-21A - 500V	800 A

Operational current - AC-21A - 690V	800 A
Operational current - AC-22A - 400/415V	800 A
Operational current - AC-22A - 500V	800 A
Operational current - AC-22A - 690V	800 A
Operational current - AC-23A - 400/415V	800 A
Operational current - AC-23A - 500V	800 A
Operational current - AC-23A - 690V	800 A
Operational current - AC-23A - 1000V	400 A

RATED OPERATIONAL POWER FOR 3-PHASE (1500 R.P.M.) SQUIRREL CAGE INDUCTION MOTORS (KW)

Operational power - AC-23A - 400/415V	400 kW
Operational power - AC-23A - 500V	560 kW
Operational power - AC-23A - 690V	800 kW

RATED FUSED SHORT CIRCUIT CURRENT


Back-up fuse	800 A
R.M.S value, IK	100
Peak value	76 kA
Rated impulse withstand voltage Uimp	12 kV
Rated short circuit making capacity at 690V, Icm	60
Rated short time withstand current at 690V (1 s), Icw	28

RATED BREAKING CAPACITY, ICN


Breaking capacity - AC-23A - 400/415V	6400 A
Breaking capacity - AC-23A - 500V	6400 A
Breaking capacity - AC-23A - 690V	6400 A

ADDITIONAL DETAILS

Electrical endurance	2000 operations
Mechanical endurance	10000 operations
Max terminal torque	50-75
Tariff code	85365080
Country of origin	FI



With SV800 kit



Standard