

POLYCARBONATE ENCLOSURES

32006-KATKO
 KEM 3630 YR MF04, Polycarbonate Enclosure,
 Yellow/Red, 3-Pole, 630A

- 10-630A switch ratings
- Other switch configurations available on request
- Wide operating temperature
- Tested to IEC 60947-3



PRODUCT DESCRIPTION

Switch Disconnectors housed in high-quality polycarbonate enclosures.
 All polycarbonate enclosures are IP66 rated at a minimum for robust protection against dust and water.
 Available in both black/grey and yellow/red.

These enclosures are self-extinguishing with a wide operating temperature range, as well as both UV and chemical resistant for long-lasting durability.

Tested to IEC 60947-3.

Note! Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector.

TECHNICAL DATA

GENERAL DATA

Number of poles	3
Rated insulation voltage Ui	1000 V
Rated thermal current, Ith	630 A
Enclosure dimensions	760x560x250mm
Terminals / Bolt size Cu	M12
Nominal values with cable size	2x185
Weight	21 kg

RATED OPERATIONAL CURRENT, IE

Operational current - AC-21A - 400/415V	630 A
Operational current - AC-21A - 500V	630 A

Operational current - AC-21A - 690V	630 A
Operational current - AC-22A - 400/415V	630 A
Operational current - AC-22A - 500V	630 A
Operational current - AC-22A - 690V	630 A
Operational current - AC-23A - 400/415V	630 A
Operational current - AC-23A - 500V	630 A
Operational current - AC-23A - 690V	630 A

RATED OPERATIONAL POWER FOR 3-PHASE (1500 R.P.M.) SQUIRREL CAGE INDUCTION MOTORS (KW)

Operational power - AC-23A - 400/415V	355 kW
Operational power - AC-23A - 500V	400 kW
Operational power - AC-23A - 690V	630 kW

RATED FUSED SHORT CIRCUIT CURRENT

Back-up fuse	630 A
R.M.S value, IK	100
Peak value	76 kA
Rated impulse withstand voltage Uimp	8 kV
Rated short circuit making capacity at 690V, Icm	60
Rated short time withstand current at 690V (1 s), Icw	28

RATED BREAKING CAPACITY, ICN

Breaking capacity - AC-23A - 400/415V	5040 A
Breaking capacity - AC-23A - 500V	5040 A
Breaking capacity - AC-23A - 690V	5040 A

ADDITIONAL DETAILS

Electrical endurance	2000 operations
Mechanical endurance	10000 operations
Max terminal torque	50-75
Tariff code	85365080
Country of origin	FI
Switch colour	Red/yellow

