OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

POLYCARBONATE ENCLOSURES

32432
KEM 4250 MF03, Polycarbonate Enclosure, 4-pole, 250A



- 10-630A switch ratings
- Other switch configurations available on request
- Wide operating temperature
- Tested to IEC 60947-3

PRODUCT DESCRIPTION

Switch Disconnectors housed in high-quality polycarbonate enclosures.
All polycarbonate enclosures are IP66 rated at a minimum for robust protection against dust and water.
Available in both black/grey and yellow/red.

These enclosures are self-extinguishing with a wide operating temperature range, as well as both UV and chemical resistant for long-lasting durability.

Tested to IEC 60947-3.
Note! Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector.

TECHNICAL DATA

GENERAL DATA

Number of poles	4
Rated insulation voltage Ui	1000 V
Rated thermal current, Ith	315 A
Enclosure dimensions	560x380x180mm
Terminals / Bolt size Cu	M10
Nominal values with cable size	120
Weight	8.3 kg

RATED OPERATIONAL CURRENT, IE

Operational current - AC-21A - 400/415V	250 A
Operational current - AC-21A - 500V	250 A
Operational current - AC-21A - 690V	250 A

Operational current - AC-22A - 400/415V	250 A
Operational current - AC-22A - 500V	250 A
Operational current - AC-22A - 690V	250 A
Operational current - AC-23A - 400/415V	250 A
Operational current - AC-23A - 500V	250 A
Operational current - AC-23A - 690V	250 A
Operational current - AC-23A - 1000V	135 A

RATED OPERATIONAL POWER FOR 3-PHASE (1500 R.P.M.) SQUIRREL CAGE INDUCTION MOTORS (KW)

Operational power - AC-23A - 400/415V	132 kW
Operational power - AC-23A - 500V	160 kW
Operational power - AC-23A - 690V	250 kW

RATED FUSED SHORT CIRCUIT CURRENT

Back-up fuse	250 A
6339_R.M.S value, IK (kA)	100
Peak value	26 kA
Rated impulse withstand voltage Uimp	8 kV
5530_Rated short circuit making capacity at 690V, Icm (kA)	14
5809_Rated short time withstand current at 690V (1 s), Icw (kA)	8


RATED BREAKING CAPACITY, ICN

Breaking capacity - AC-23A - 400/415V	2000 A
Breaking capacity - AC-23A - 500V	2000 A
Breaking capacity - AC-23A - 690V	2000 A

ADDITIONAL DETAILS

Electrical endurance	2000 operations
Mechanical endurance	16000 operations
4950_Max terminal torque (Nm)	15-22
Tariff code	85365080
Country of origin	FI

Switch colour	Black/grey


380
354
534
560
240
180