

## FIRE-RATED SWITCH DISCONNECTORS

30536

KEA 440 FR A2, Aluminium Box, 4P, 40A

- Conform to F200 (FR) or F300 (FR3) smoke and heat standard under EN12101-3
- IP65/66
- Tested according to IEC 60947-3



### PRODUCT DESCRIPTION

Fire Rated Isolators from Katko are designed to conform to F200 (FR) or F300 (FR3) class of EN 12101-3 smoke and heat standard at 200°C for 3 hours. The enclosures are available in aluminium or stainless steel and are IP65/66 rated for protection against water and dust. Handles are padlockable with a defeat mechanism.

## TECHNICAL DATA

### GENERAL DATA

Rated insulation voltage Ui	800 V
Rated thermal current, Ith	63 A
Terminals / Bolt size Cu	1.5-16

### RATED OPERATIONAL CURRENT, IE

Operational current - AC-21A - 400/415V	63 A
Operational current - AC-21A - 500V	63 A
Operational current - AC-21A - 690V	63 A
Operational current - AC-22A - 400/415V	40 A
Operational current - AC-22A - 500V	40 A
Operational current - AC-22A - 690V	40 A
Operational current - AC-23A - 400/415V	40 A
Operational current - AC-23A - 500V	32 A

Operational current - AC-23A - 690V	32 A
-------------------------------------	------

## RATED FUSED SHORT CIRCUIT CURRENT

R.M.S value, IK	50
Rated impulse withstand voltage Uimp	8 kV
Rated short circuit making capacity at 690V, Icm	2.5
Rated short time withstand current at 690V (1 s), Icw	1.7

## RATED BREAKING CAPACITY, ICN

Breaking capacity - AC-23A - 400/415V	320 A
Breaking capacity - AC-23A - 500V	256 A
Breaking capacity - AC-23A - 690V	256 A

## ADDITIONAL DETAILS

Electrical endurance	3000
Mechanical endurance	50000
Max terminal torque	1.8