OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

FIRE-RATED SWITCH DISCONNECTORS

33342
KEA 325 FR3 A2, F300 Aluminium, 3P, 25A



- Conform to F200 (FR) or F300 (FR3) smoke and heat standard under EN12101-3
- IP65/66
- Tested according to IEC 60947-3

PRODUCT DESCRIPTION

Fire Rated Isolators from Katko are designed to conform to F200 (FR) or F300 (FR3) class of EN 12101-3 smoke and heat standard at 200°C for 3 hours. The enclosures are available in aluminium or stainless steel and are IP65/66 rated for protection against water and dust. Handles are padlockable with a defeat mechanism.

TECHNICAL DATA

GENERAL DATA

Rated insulation voltage Ui	800 V
Rated thermal current, Ith	40 A
Terminals / Bolt size Cu	1.5-16

RATED OPERATIONAL CURRENT, IE

Operational current - AC-21A - 400/415V	40 A
Operational current - AC-21A - 500V	40 A
Operational current - AC-21A - 690V	40 A
Operational current - AC-22A - 400/415V	25 A
Operational current - AC-22A - 500V	25 A
Operational current - AC-22A - 690V	25 A
Operational current - AC-23A - 400/415V	25 A
Operational current - AC-23A - 500V	25 A
Operational current - AC-23A - 690V	25 A

RATED FUSED SHORT CIRCUIT CURRENT

6339_R.M.S value, IK (kA)	50
Rated impulse withstand voltage Uimp	8 kV
5530_Rated short circuit making capacity at 690V, Icm (kA)	2.5
5809_Rated short time withstand current at 690V (1 s), Icw (kA)	1.7

RATED BREAKING CAPACITY, ICN

Breaking capacity - AC-23A - 400/415V	200 A
Breaking capacity - AC-23A - 500V	200 A
Breaking capacity - AC-23A - 690V	200 A

ADDITIONAL DETAILS

Electrical endurance	3000
Mechanical endurance	50000
4950_Max terminal torque (Nm)	1.8