

## MINIMOTOR - PCFSS STAINLESS STEEL WORM GEAR MOTOR

PCFSS 80/50-75  
230V 75rpm 13.9 Nm

- IP69K sealing
- Full stainless steel outer parts
- Up to 18Nm rated torque
- Brushless AC with resolver feedback



### PRODUCT DESCRIPTION

Motor: 4 pole sinusoidal brushless, featuring NdFeB rare earth magnets and sealed in stainless steel housing.

Thermal protection, Class H winding and IP69K protection according to IEC/EN 60529 standards.

2 pole resolver for feedback. Roller bearings with reduced backlash for smoother operation and high temperature grease.

Gear unit: Stainless steel body, bronze crown gear. Tempered steel screw rotating on spherical ball bearings and lubricated with NSF-H1 oil for a long life.

Rated torque 80Nm.


Designed as per EHEDG hygiene guidelines requirements

[Please click here for 2D and 3D drawings.](#)

### TECHNICAL DATA

Input voltage ac	230V
IP class	IP69K

Nominal speed	75 rpm
Nominal torque	13.9
Output power	180 W
Rated current	1.48 A
Ratio	40:1





Type Type Type Type	A	B	C	D	E	F	G	H	I	L	L1	L2
PCFSS5550	37	29	19	14	M8x11	5	16,3	40	30	297,5	39	55,5
PCFSS8050	37	29	19	14	M8x11	5	16,3	40	30	302,5	39	55,5


Type Type Type Type	L3	M	N	P	Q	R	S	T	U	V	Z	Press Mount Gears/End Flange Pitch No.
PCFSS5550	164,5	115	57	64	68	33,5	55	90	47,5	93	M8x7	6,80
PCFSS8050	169,5	115	57	64	90	33,5	55	90	60,5	93	M8x7	9,10


PCF model selection


 Electric motor  
15.06.2017

 Geared motor  
15.06.2017


 Worm gearmotor  
15.06.2017

 Brushless servomotor  
15.06.2017

 Clean products  
15.06.2017

 Controls  
15.06.2017

Please see product description above for 2D and 3D drawings



Type Type Type Type	A	B	C	D	E	F	G	H	I	L	L1	L2
PCFSS5550	37	29	19	14	M8x11	5	16,3	40	30	297,5	39	55,5
PCFSS8050	37	29	19	14	M8x11	5	16,3	40	30	302,5	39	55,5

Type Type Type Type	L3	M	N	P	Q	R	S	T	U	V	Z	Press Mount Gears/End Flange Pitch No.
PCFSS5550	164,5	115	57	64	68	33,5	55	90	47,5	93	M8x7	6,80
PCFSS8050	169,5	115	57	64	90	33,5	55	90	60,5	93	M8x7	9,10

PCF model selection

 Electric motor  
15.06.2017

 Geared motor  
15.06.2017

 Worm gearmotor  
15.06.2017

 Brushless servomotor  
15.06.2017

 Clean products  
15.06.2017

 Controls  
15.06.2017

Please see product description above for 2D and 3D drawings