

## ECO MULTIFUNCTION TIMER

MFR

16373.2

MFR-7 MF TIMER 24-240VAC/DC 5A, 1PCO Eco

- 17.5mm wide
- Time Range 0.05 sec - 10 Hours
- 7 functions
- 24...48vdc,/24...240vac Supply
- 1 x 5A change-over contact

### PRODUCT DESCRIPTION

## TECHNICAL DATA

Basic accuracy	<1,5%(of the range)
Colour	Light gray
Connection type	Screw
Contact material	AgNi
Continuous current max / Inrush current max	5 / 5 A
Control contact terminals	A1-B1
Country of origin	AT
Cross section single wire from	2.5 mm <sup>2</sup>
Cross section single wire to	0.25 mm <sup>2</sup>
Cross section stranded with ferrule from	0.25 mm <sup>2</sup>
Cross section stranded with ferrule to	1.5 mm <sup>2</sup>
Electrical life in hours (AC1)	1x10 <sup>5</sup>
Fuse	5 A
Height TS 35 / 7.5 with base	57.9 mm
Length	90 mm
Mechanical life hours	1x10 <sup>6</sup>
Nominal frequency min	48 Hz
Number of functions	6
Pack size	10
Rated contact voltage	250V ac

<b>Rated frequency max</b>	63 Hz
<b>Relay contact</b>	1 CO
<b>Repeatability accuracy</b>	<0,5% / ± 5 ms
<b>Setting accuracy</b>	<5% (of the range)
<b>Stripping length</b>	7 mm
<b>Supply voltage</b>	24...240 ac, 24...48 ac/dc
<b>Switching voltage max</b>	250 v ac
<b>Tariff code</b>	85364900
<b>Temperature influence</b>	<0,05% / °C
<b>Time range</b>	50 ms - 10 h
<b>Tolerance</b>	-15% / 10%
<b>Torque</b>	0.5
<b>Weight</b>	42.3 g
<b>Width</b>	17.5 mm

