OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ECO MULTIFUNTION TIMER

MFR

16373.2
MFR-7 MF TIMER 24-240VAC/DC 5A, 1PCO Eco



- 17.5mm wide
- Time Range 0.05 sec - 10 Hours
- 7 functions
- 24…48vdc,/24…240vac Supply
- 1 x 5A change-over contact

PRODUCT DESCRIPTION

TECHNICAL DATA

Basic accuracy	<1,5%(of the range)
Colour	Light gray
Connection type	Screw
Contact material	AgNi
Continuous current max / Inrush current max	5 / 5 A
Control contact terminals	A1-B1
Country of origin	AT
Cross section single wire from	2.5 mm²
Cross section single wire to	0.25 mm²
Cross section stranded with ferrule from	0.25 mm²
Cross section stranded with ferrule to	1.5 mm²
Electrical life in hours (AC1)	$1x10^5$
Fuse	5 A
Height TS 35 / 7.5 with base	57.9 mm
Length	90 mm
Mechanical life hours	$1x10^6$
Nominal frequency min	48 Hz

Number of functions	6
Pack size	10
Rated contact voltage	250V ac
Rated frequency max	63 Hz
Relay contact	1 CO
Repeatability accuracy	<0,5% / ± 5 ms
Setting accuracy	<5% (of the range)
Stripping length	7 mm
Supply voltage	24…240 ac, 24…48 ac/dc
Switching voltage max	250 v ac
Tariff code	85364900
Temperature influence	<0,05% / °C
Time range	50 ms - 10 h
Tolerance	-15% / 10%
Torque	0.5
Weight	42.3 g
Width	17.5 mm

