

DIN TIMER SOLID STATE OUTPUT

Chronos 2 Series

88827054

Timer MLS2 Recycling Solid State 24-240V ac

- 17.5mm wide
- Time range 0.1 sec – 100 hrs
- Wide range supply voltage
- Solid state output



PRODUCT DESCRIPTION

Chronos 2 series timer relays for DIN rail mounting with screw terminal connections and these versions have a 0.7A rated solid state output in a 17.5mm wide housing.

Time range is adjustable (in sub ranges) from 0.1 sec to 100 hours using a selector switch and potentiometer on the front face of the device.

A wide range supply voltage covers most requirements in the standard units.

Some units are single function and some are multi function with the required timing function set by a selector switch on the front face of the device. The available timing functions are defined by a set of letter codes that is common across the whole Crouzet range.

TECHNICAL DATA

Approvals	CE, Lloyd's, RoHS, UL
Breaking capacity	0,7 A
Cable area with sleeve	2 x 1,5 mm ²
Cable area without sleeve	2 x 2,5 mm ²
Close delay	50 ms
Electrical lifetime	108 operations
Function	L, Li
IP class connection	IP20
IP class front	IP50
Mounting	DIN rail

Multi-function	No
Output	Solid state
Power min	0.01 A
Repeatability	0.5 %
Response time off	350 ms
Storage temperature max	60 °C
Storage temperature min	-30 °C
Supply voltage	24-240V AC
Switching current max	0.7 A
Temperature operational max	60 °C
Temperature operational min	-20 °C
Time range	0,1-1s, 1-10s, 6-60s, 1-10min, 6-60min, 1-10h, 10-100h

